



PART NO.	Current Rating	Dimension
		Ø A
1198-133-715-000	40 AMPS	Ø4.60
1198-133-515-000	30 AMPS	Ø3.3
1198-133-315-000	20 AMPS	Ø2.8
1198-133-115-000	10 AMPS	Ø1.7

MATERIALS AND FINISH

SHELL : STEEL MATERIAL, TIN FINISHED
 CONNECTOR INSULATOR : PBT THERMOPLASTIC,
 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR
 SIGNAL CONTACT MATERIAL: BRASS, FULL GOLD FLASH
 HIGH POWER CONTACT MATERIAL: BRASS, 15u" GOLD PLATED

ELECTRICAL CHARACTERISTICS

HIGH POWER CONTACT CURRENT RATING :10,20,OR 40 AMPS
 HIGH POWER CONTACT RESISTANCE : 2.7 MILLIOHMS MAX.
 DIELECTRIC WITHSTANDING VOLTAGE :
 1000 V AC FOR 1 MINUTE
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.
 TEMPERATURE RATING : -55°C ~ +125°C

CAZN 正成
 深圳市正成电气有限公司
 Shenzhen Cazan Electronic Co., Ltd.

Drawn by	liuqiong	2002.05.10
Designed by	liuqiong	2002.05.10
Approved by	yangjinguo	2002.05.10
	Sheet 1 of 1	Code 000
Dimensions in mm(inches)		Scale 1:1
Tolerances on:XX+/-0.13		Angles+/-2°

D-SUB CONNECTOR
 (Power Contact Solder Type)

Ver A0 Part No: 1198-133-X15-003