



Matters needing attention in production

General Specifications	
Wire specifications	32/24AWG
Contact quantity	9
Temperature range	-25°C~+80°C
Withstand voltage	≥DC300V
Insulation resistance	≥10MΩ DC300V

Pin Assignment 接线定义		
P1	Wire Color 线性颜色	P2
A4.A9	Red 红	A4.A9
B4.B9		B4.B9
A7	White 白	A7
A6	Green 绿	A6
A1.A12	Black 黑	A1.A12
B1.B12		B1.B12
B10	Orange 橙	A3
B11	violet 紫	A2
A5	Yellow 黄	A5
A3	Yellow 黄	B10
A2	Blue 蓝	B11
Shell 外壳	Shield Braid 屏蔽编织	Shell 外壳

1 Custom Snap on TYPE-C3.0 male plug to TYPE-C3.0 male plug, harness total length L = 1m (including connectors) , TYPE-C , use TYPE-C3.0 CM (C TO C) and TYPE-C3.0 CM (C TO C) , cable using UL2725 32AWG*1P+D+AL)*2+32AWG*1P+32AWG*2C+24AWG*2C+ADB covered with black PVC, OD: 4.5, wiring definition:
 A4. A9. B4. B9-A4. A9. B4. B9-red, A7-A7-white, A6-A6-green, A1. B1. A12. B12-A1. B1. A12. B12-black, B10-A3-orange, B11-A2-violet, A5-A5-yellow, A3-B10-yellow, A2-B11-blue, shell-shell-weave shield, we offer an E10 Snap on connection nut and an E10TP waterproof gasket Φ14-8.4-2.7-1.2

No.	Specification	Unit	Q'ty
	GENERAL TOLERANCE (UNLESS SPECIFIED)		
	≤10 ±0.1		
	<10~≤20 ±0.2		
	<20~≤50 ±0.5		
	Angle ±3'		
	DWN		
	CHK		
	APVD		
	UNIT MM	REV A	
	SIZE A4	SHEET 1 OF 1	
	THIRD ANGLE		
	TITLE E10B-MT3-MWA/NWA-1PV-S		
	PART NO 2CA2-E10 C3-BA-M/C3-A-M-1M		
	DRAWING NO C130505-00029		

Statement: Please confirm and return the drawings within 2 working days. If the drawings are not returned after the expiration date, the default is that you have been confirmed to be qualified.

Business confirmation

RoHS

Customer	DWN NO	DATE	DWN	APVD
P/N		2024-03-08	Junming. Hu	
Product Name		UNIT: mm	Size:A4	