



Matters needing attention in production

General Specifications	
Wire specifications	32/24AWG
Contact quantity	9
Temperature range	-25℃~+80℃
Withstand voltage	≥DC300V
Insulation resistance	≥10MΩ DC300V

Pin Assignment 接线定义		
P1	Wire Color 线性颜色	P2
A4.A9 B4.B9	Red 红	A4.A9 B4.B9
A7	White 白	A7
A6	Green 绿	A6
A1.A12 B1.B12	Black 黑	A1.A12 B1.B12
B10	Orange 橙	A3
B11	violet 紫	A2
A5	Yellow 黄	A5
A3	Yellow 黄	B10
A2	Blue 蓝	B11
Shell 外壳	Shield Braid 屏蔽编织	Shell 外壳

Stranded wire
Stranded wire
Stranded wire

1 Custom twisted cord TYPE-C3.0 male plug to TYPE-C3.0 male plug, harness total length L = 2m (including connectors) , TYPE-C , use TYPE-C3.0 CM (C TO C) and TYPE-C3.0 CM (C TO C) , cable using UL2725 32AWG*1P+D+AL)*2+32AWG*1P+32AWG*2C+24AWG*2C+ADB covered with black PVC, OD: 4.5, wiring definition:
A4. A9. B4. B9-A4. A9. B4. B9-red, A7-A7-white, A6-A6-green, A1. B1. A12. B12-A1. B1. A12. B12-black, B10-A3-orange, B11-A2-violet, A5-A5-yellow, A3-B10-yellow, A2-B11-blue, shell-shell-weave shield, we offer an E10 threaded connection nut and an E10TP waterproof gasket Φ14-8.4-2.7-1.2

pc 1

深圳市正成电气有限公司
受控文件



Statement: Please confirm and return the drawings within 2 working days. If the drawings are not returned after the expiration date, the default is that you have been confirmed to be qualified.

Business confirmation

Customer	DWN NO	DATE	DWN	APVD
P/N		2024-01-16	Junming. Hu	
Product Name		UNIT: mm	Size:A4	

RoHS

No.	Specification	Unit	Q'ty
	GENERAL TOLERANCE (UNLESS SPECIFIED)		
	≤10 ±0.1		
	<10~≤20 ±0.2		
	<20~≤50 ±0.5		
	Angle ±3'		
	THIRD ANGLE		
	DWN		
	CHK		
	APVD		
	UNIT	REV	TITLE
	MM	A	E10T-MT3-MWA/NWA-2PV-S
	SIZE	SHEET	PART NO
	A4	1 OF 1	2CA2-E10 C3-TA-M/C3-A-M-2M
			DRAWING NO
			C130505-00050