

面板开孔尺寸

Technical specifications:


Materials:


Coupling:	Coupling connection	Shell material:	PA66+GF UL94 Black
Mating cycles:	≥500	Sealing material:	Silica gel Black
Degree of protection:	IP67	Contact material:	Zirconia
Flame retardant grade:	UL94-V0	<p style="text-align: center;">Ambient condition</p> <p>operation temperature: -25℃~80℃</p> <p>Storage temperature: -5℃~65℃</p> <p>atmospheric pressure: (86~106) kPa</p> <p>Relative humidity: ≤90%</p>	
Transfer rate:	10Gb/s		
Repeatability:	≤0.1db		
Insertion loss:	≤0.2db		
Return Loss:	≤0.1db		
Interchangeability:	≤0.2db		
Maximum Insertion Loss:	≤0.3db		
Wavelength:	1200~1600nm		

4	E16 waterproof sealing gasket	silica gel	/	pcs	1
3	1"-20UNEF hexagon nut	Nylon	/	pcs	1
2	E16 After the snap on board, the mother seat fiber optic plastic shell	Nylon	/	pcs	1
1	GXSC Welding single link earless clip adapter, AD-SC-CP-SX-02	/	/	pcs	1
No.	Specification	Material	Treat	Unit	Q'ty

GENERAL TOLERANCE (UNLESS SPECIFIED)

≤10	±0.1
<10~≤20	±0.2
<20~≤50	±0.5
Angle	±1°



DWN	
CHK	
APVD	
UNIT MM	REV A
SIZE A4	SHEET 1 OF 1

TITLE
C130204-00007

PART NO
E16B-FF1-PRF

DRAWING NO