



技术参数		材料	
连接方式:	耦合连接	插芯材料:	氧化锆
插拔次数:	≥500	外壳材料:	高性能工程塑料
防水等级:	IP67	防水圈:	硅胶
阻燃等级:	UL94-V0		
传输速度:	10Gb/s	环境条件	
重复性:	≤0.1db	工作温度:	-25℃~80℃
插入损耗:	≤0.2db	储存温度:	-5℃~65℃
回波损耗:	≤0.1db	大气压力:	(86~106) kPa
互换性:	≤0.2db	相对湿度:	≤90%
最大插入损耗:	≤0.3db		
波长:	1200~1600nm		

产品型号	L (mm)
E13FDDI-A-LC/LC-1M	1000±30
E13FDDI-A-LC/LC-2M	2000±30
E13FDDI-A-LC/LC-3M	3000±30

GENERAL TOLERANCE (UNLESS SPECIFIED)	DWN		
	CHK		
	APVD		
$\leq 10 \pm 0.1$ $< 10 \sim \leq 20 \pm 0.2$ $< 20 \sim \leq 50 \pm 0.5$ Angle $\pm 1^\circ$	TITLE	LC双工 E13塑胶插头	
 THIRD ANGLE	UNIT MM	REV A	PART NO
	SIZE A4	SHEET 1 OF 1	DRAWING NO E13FDDI-A-LC/LC