



Dimensions of panel openings

Technical specifications:		Materials:	
Connect Mode:	Coupling connection	Core material:	White oxide
Mating cycles:	≥500	Canning material:	High Performance Engineering Plastics
Waterproof grade:	IP67	Waterproof ring:	silica gel
Flame retardant grade:	UL94-V0		
Transmission speed:	10Gb/s	Environmental conditions	
Repeatability:	≤0.1db	Operating temperature:	-25°C~80°C
Insertion loss:	≤0.2db	Storage temperature:	-5°C~65°C
Return Loss:	≤0.1db	Barometric pressure:	(86~106) kPa
Interchangeability:	≤0.2db	Relative humidity:	≤90%
Maximum insertion loss:	≤0.3db		
Wave length:	1200~1600nm		

No.	Specification	Material	Treat	Unit	Q'ty
4	E13 Pedestal waterproof gasket 24*20.6*1.5	Silica gel	Black	pc	1
3	E13 Hex flange nut	PA66	Black/Blue	pc	1
2	E13 Threaded plate rear fiber body	PA66	Black	pc	1
1	Optical fiber simplex core(SC-SC)	/	/	pc	1

GENERAL TOLERANCE (UNLESS SPECIFIED) ≤10 ±0.1 <10~≤20 ±0.2 <20~≤50 ±0.5 Angle ±1°	DWN	
	CHK	
	APVD	
	TITLE SC Simplex adapter E13 Threaded plate rear socket	
	PART NO	
 THIRD ANGLE	UNIT MM	REV A
	SIZE A4	SHEET 1 OF 1
	DRAWING NO E13FDDI-TF-SC	