



| | | | | | |
|-----|--|---|-------------------|------|------|
| 7 | E13 防尘帽防水圈 19.6*1.5 E13 Dust cap waterproof ring 19.6*1.5 | 硅胶 silica gel | 黑色 Black | pc | 1 |
| 6 | E13 螺牙防尘盖 E13 Screw dust cover | 塑胶 plastic | 黑/蓝 Black/blue | pc | 1 |
| 5 | E10 防尘帽插条 E10 Dust cap insert | PE | 黑色 Black | pc | 1 |
| 4 | E13 法兰螺母 E13 flange nut | PA66 | 黑/蓝 Black/blue | pc | 1 |
| 3 | E13 板前板后防水圈 24.8*1.5 E13 Waterproof ring 24.8*1.5 | 硅胶 silica gel | 黑色 Black | pc | 1 |
| 2 | RJ45板后主体 RJ45 back mounting body | PA66 | 黑色 Black | pc | 1 |
| 1 | RJ45双网口90度 RJ45 dual network port 90° | RJ网口+PCB板 RJ network port +PCB board | 镀金 gold plated | pc | 1 |
| No. | Specification | Material | Treat | Unit | Q'ty |

技术参数(Technical specifications):

| | |
|--------------------------------|---|
| 传输速率: transmission rate | 符合TIA或EIA 568B的5E类/6A类D级/等级和符合ISO/IEC 11801 CAT5E/6A ,According to TIA or EIA 568B,According to ISO/IEC 11801 |
| 防水等级: Degree of protection | IP67 |
| 接触电阻: Contact resistance | $\cong 20m\Omega$ |
| 绝缘电阻: Insulation resistance | $\cong 500M\Omega$ at DC500V |
| 工频耐电压: Withstand voltage | $\cong AC 1000V / 1$ 分钟 $\cong AC 1000V / 1$ minute |
| 盐雾腐蚀: Salt spray corrosion | 48小时 48 hours |
| POE: | 60W / 2A |

| | | | | |
|--|------------|-----------------|------------|------------------------|
| GENERAL TOLERANCE (UNLESS SPECIFIED) | DWN | | | |
| | CHK | | | |
| $\leq 10 \pm 0.1$ $< 10 \sim \leq 20 \pm 0.2$ $< 20 \sim \leq 50 \pm 0.5$ Angle $\pm 1^\circ$ | APVD | | | TITLE RJ45-F-S/S-90 |
| | UNIT MM | REV A | | PART NO |
| | SIZE A4 | SHEET 1 OF 1 | DRAWING NO | |